

• Hardware

Comm. Controller	MU860 (16C550C compatible)
Bus	32-bit Universal PCI
Connector	DB44 female

• Serial Interface

Number of Ports	4
Serial Standards	2 x RS-232/422/485, 2 x RS-422/485
Max. No. of Boards per PC	8

• Serial Line Protection

Electrical Isolation	2 kV (CP-134U-I configured for RS-422/485 only)
----------------------	---

• Performance

Baudrate	50 bps to 921.6 kbps (supports non-standard baudrates)
----------	--

• Serial Communication Parameters

Data Bits	5, 6, 7, 8
Stop Bits	1, 1.5, 2
Parity	None, Even, Odd, Space, Mark
Flow Control	RTS/CTS, XON/XOFF, RTS Toggle (RS-232 only)

• Serial Signals

RS-232	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
RS-422	TxD+(B), TxD-(A), RxD+(B), RxD-(A), RTS+(B), RTS-(A), CTS+(B), CTS-(A), GND
RS-485-4w	TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND
RS-485-2w	Data+(B), Data-(A), GND

• Physical Characteristics

Dimensions	CP-134U: 82.5 x 120 mm (3.24 x 4.72 in) CP-134U-I: 115 x 120 mm (4.52 x 4.72 in)
------------	---

• Driver Support

Windows	Windows 95/98/ME/NT/2000, Windows XP/2003/Vista/2008/7/8/8.1/10 (x86/x64), Windows Server 2008 R2/2012/2012 R2/2016 (x64), DOS, Windows Embedded CE 5.0/6.0, Windows XP Embedded
---------	--